

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
10 March 2005 (10.03.2005)

PCT

(10) International Publication Number
WO 2005/022876 A1

(51) International Patent Classification⁷: **H04M 3/22**,
H04B 3/46, 3/23, H04M 9/08

Martijn [NL/NL]; Van Diemenstraat 60, NL-2518 VD The Hague (NL).

(21) International Application Number:
PCT/EP2004/009299

(74) Agent: **WUYTS, Koenraad, Marla**; Koninklijke KPN N.V., P.O. Box 95321, NL-2509 CH The Hague (NL).

(22) International Filing Date: 18 August 2004 (18.08.2004)

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/498,525 28 August 2003 (28.08.2003) US

(71) Applicant (for all designated States except US): **KONINKLIJKE KPN N.V.** [NL/NL]; Stationsplein 7, 9726 AE Groningen (NL).


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,

(72) Inventor; and

(75) Inventor/Applicant (for US only): **VAN VUGT, Jeroen**,

[Continued on next page]

(54) Title: MEASURING A TALKING QUALITY OF A COMMUNICATION LINK IN A NETWORK



(57) Abstract: Device and method for measuring a talking quality of a communication link in a communications network (10). The device comprises measurement means (22; 31, 36) connected to the communication link, which are arranged to subject a degraded speech signal $s'(t)$ with respect to a reference speech signal $s(t)$ to an objective measurement technique for measuring a perceptual quality of speech signals. Furthermore, the measurement means are arranged for producing a quality signal (q) which represents an estimated value concerning the talking quality degradation. The degraded speech signal comprises a returned signal $r(t)$. The measurement means (22; 31, 36) are arranged to execute the objective measurement technique by modelling masking effects in consequence of noise present in the returned signal. The objective measurement technique comprises the determination of a threshold noise level by determining a local minimum value of the degraded speech signal $s'(t)$.



FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,
SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

Declaration under Rule 4.17:

— of inventorship (Rule 4.17(iv)) for US only

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.